



PLAN - FOOTINGS
150

FOOTING BEAM SCHEDULE				
MARK	DEPTH	WIDTH	REINFORCEMENT	COVER
E+	250	300	2N12 2N12	W6-600 50

- SLAB [130] 130 THICK SL72 TOP 30 COVER
SL72 BOTTOM 40 COVER
- 300 SQUARE x600 DEEP MASS CONCRETE PAD
- 1200 LONG INTEGRAL PIER FOUNDED AT LEAST 300mm INTO FIRM NATURAL GROUND 4N16 VERTICAL BARS ONE IN EACH CORNER

- NOTES:
1. READ THIS DRAWING TOGETHER WITH THE ARCHITECTURAL DWGS FOR ALL SET OUT DIMENSIONS
 2. CONCRETE STRENGTH SHALL BE GRADE N32 FOR SLAB GRADE N25 FOR STRIPS AND PADS
 3. LAPS TO REINFORCEMENT SHALL BE:
FABRIC ONE FULL MESH PLUS 25mm
BARS N12 - 500mm

Dean Iuliano & Company
Consulting Engineers structural - civil

100 Rundle Street KENT TOWN SA 5067
Tel (08) 8363 3900 Fax (08) 8362 7930
Email diuleng@bigpond.net.au

NEW VISITOR AMENITIES
KANGAROO ISLAND SA
KANGAROO ISLAND COUNCIL